

ÜBERSICHT BANDSYSTEME

	Bandgeschwindigkeit [m/min]	Spurbreite [mm]	Empfohlenes Werkstückträgergewicht [kg]	Bandgeschwindigkeit [m/min]	Spurbreite [mm]	Empfohlenes Werkstückträgergewicht [kg]
MTS 1	BS1	5	–	25		5,5
	BS2/3	20	100	45		5,5
	BS4/5	30	100	100–400		5,5
	BS6/7	50	150	200–800		5,7
	BS200	–	100	200–1000		8,2
MTS 2	BS37	–	500	bis 7,5 44,5–190,5		0–50
	BS81	–	450	bis 8 50		0–15
	BS86	–	500	bis 8 82,2		30–50
MTS 3	BS11	250	750	5–17 160–800		20–100
	BS20	75	200	5–16 160–640		10–50
	BS21	60	70	10–15 160–240		0–20
	BS35	50	80	8–15 160–800		5–30
	BS55	150	250	7–14 160–800		10–100
	BS100	350	1000	8–16 240–800		50–250
	BS300	100	750	8–16 300–800		10–100
	Belastung pro Meter [kg]	Belastung pro Antrieb [kg]	Weitere Ausführungen auf Anfrage.			

Bandgeschwindigkeit [m/min]



Spurbreite [mm]



Empfohlenes Werkstückträgergewicht [kg]
(= Werkstück + -träger + -aufnahme)

